

# LED Dome Lights

Create a better ambience in any environment with V-TAC's LED Dome Lights. These Compact and Easy to install lights make a perfect replacement for traditional Dome Lights.






## Product Features

- 80% Electricity savings as compared to traditional Incandescent Bulbs
- Non - Flickering
- No UV Radiation
- Easy Installation
- Premium Quality LED Chip
- Premium Quality Power Driver
- Instant start 0-100% in 0.01 seconds
- Extreme Weather toleration (-20 to + 45 Degrees Centigrade)

## Applications

Mostly used in Parking Lots, Passage's in big areas, Exterior Walls of Prestigious Buildings for ambience, Airports, Ports and Malls.



## LED Oval Dome Light

BOX QTY.

**20**

**8W** VT-8038

EAN Code

1308 - 3000K Warm White

3800157620260



1309 - 4000K Day White

3800157620277

1310 - 6400K White

3800157620284

Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50/60Hz</b>	Body Type:	<b>PC</b>
Luminous Flux:	<b>560lm</b>	Shape:	<b>Rectangle</b>
LED Type:	<b>SMD</b>	IP Rating:	<b>IP54</b>
CRI:	<b>&gt;70</b>	Color of Fixture:	<b>Black</b>
PF:	<b>&gt;0.5</b>	Dimension:	<b>190 x 100 x 55mm</b>



## LED Oval Dome Light

BOX QTY.

**20**

**8W** VT-8038

EAN Code

1311 - 3000K Warm White

3800157620291

1312 - 4000K Day White

3800157620307

1313 - 6400K White

3800157620314

Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50/60Hz</b>	Body Type:	<b>PC</b>
Luminous Flux:	<b>560lm</b>	Shape:	<b>Rectangle</b>
LED Type:	<b>SMD</b>	IP Rating:	<b>IP54</b>
CRI:	<b>&gt;70</b>	Color of Fixture:	<b>White</b>
PF:	<b>&gt;0.5</b>	Dimension:	<b>190 x 100 x 55mm</b>



## LED Dome Light


15W VT-8033

- 1388 - 3000K Warm White
- 5566 - 4000K Day White
- 1389 - 6000K White

BOX QTY.  
10

EAN Code

- 3800157626453
- 3800157610353
- 3800157626460



Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	1250lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP44
CRI:	>80	Dimension:	Ø 220mm x 47.5mm
PF:	>0.6		

EASY TO USE  
PLUG AND PLAY

Luxurious Finish  
SURFACE MOUNTED

TRIMLESS



## LED Dome Light


15W VT-8033

- 1390 - 3000K Warm White
- 5567 - 4000K Day White
- 1391 - 6000K White

BOX QTY.  
10

EAN Code

- 3800157626477
- 3800157610360
- 3800157626484



Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	1250lm	Shape:	Square
LED Type:	SMD	IP Rating:	IP44
CRI:	>80	Dimension:	200 x 200 x 47.5mm
PF:	>0.6		

**NEW**



### LED Dome Light

**25W** VT-8066


- 1392 - 3000K Warm White
- 1393 - 4000K Day White
- 1394 - 6400K White

**BOX QTY.**



**EAN Code**

- 3800157628259
- 3800157628266
- 3800157628273



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>110°</b>
Voltage/Frequency:	<b>AC: 100-240V, 50/60Hz</b>	Body Type:	<b>PC</b>
Luminous Flux:	<b>2000lm</b>	Shape:	<b>Round</b>
LED Type:	<b>SMD</b>	IP Rating:	<b>IP44</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>Ø 300mm x 50mm</b>
PF:	<b>&gt;0.9</b>		

**EASY TO USE  
PLUG AND PLAY**

**Luxurious Finish  
SURFACE MOUNTED**

**TRIMLESS**

**NEW**



### LED Dome Light

**25W** VT-8066


- 1395 - 3000K Warm White
- 1396 - 4000K Day White
- 1397 - 6400K White

**BOX QTY.**



**EAN Code**

- 3800157628280
- 3800157628297
- 3800157628303



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>110°</b>
Voltage/Frequency:	<b>AC: 100-240V, 50/60Hz</b>	Body Type:	<b>PC</b>
Luminous Flux:	<b>2000lm</b>	Shape:	<b>Square</b>
LED Type:	<b>SMD</b>	IP Rating:	<b>IP44</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>300 x 300 x 50mm</b>
PF:	<b>&gt;0.9</b>		




## Led Dome Light

**12W** VT-8031

1414 - 3000K Warm White  
5563 - 4000K Day White  
5562 - 6500K White

**BOX QTY.**  
 **16**

EAN Code  
3800157610322  
3800157610315



Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Metal + PMMA
Luminous Flux:	800lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP20
CRI:	>80	Dimension:	Ø 250 x 80mm
PF:	>0.6		



## MAXIMUM LIGHT OUTPUT AND ENERGY EFFICIENT




## Led Dome Light

**24W** VT-8032

1415 - 3000K Warm White  
5565 - 4000K Day White  
5564 - 6500K White

**BOX QTY.**  
 **10**

EAN Code  
3800157610339  
3800157610346



Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Metal + PMMA
Luminous Flux:	1700lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP20
CRI:	>80	Dimension:	Ø 320 x 95mm
PF:	>0.6		



## Led Dome Light

16W VT-8001C


- 1281 - 3000K Warm White
- 4965 - 4500K Day White
- 1282 - 6000K White

BOX QTY.

**05**

EAN Code

- 3800157612678
- 3800230625809
- 3800157612685



*\*Can be customized*

Sensor Type:	<b>Microwave</b>	Detection Distance:	<b>*1-8m (radius)</b>
Color:	<b>White</b>	Time Delay:	<b>*10 sec to 12 min</b>
Detection Range:	<b>360°</b>	Luminous Flux:	<b>1300lm</b>
Voltage:	<b>AC:220-240V, 50/60Hz</b>	Body Type:	<b>PC Cover</b>
Rated Load:	<b>16W</b>	IP Rating:	<b>IP54</b>
Watts:	<b>16W</b>	Dimension:	<b>Ø296 x 96mm</b>



## Led Dome Light

Max. 60W VT-8002C


4966

BOX QTY.

**05**

EAN Code

3800230625816



*\*Can be customized*

Sensor Type:	<b>Microwave</b>	Detection Distance:	<b>*1-8m (radius)</b>
Color:	<b>White</b>	Time Delay:	<b>*10 sec to 12 min</b>
Detection Range:	<b>360°</b>	Body Type:	<b>ABS+Plastic+PC</b>
Voltage:	<b>AC:220-240V, 50/60Hz</b>	IP Rating:	<b>IP44</b>
Rated Load:	<b>Uses Max. 60W(E27)</b>	Dimension:	<b>Ø296 x 96mm</b>
Watts:	<b>As per E27 bulb</b>		



## Led Dome Light


12W VT-8017

- 5057 - 3000K Warm White
- 5058 - 4000K Day White
- 5059 - 6400K White

**BOX QTY.**  
**10**

EAN Code

- 3800157605250
- 3800157605267
- 3800157605274



Sensor Type:	<b>PIR Sensor</b>
Color:	<b>White</b>
Detection Range:	<b>360°</b>
Voltage:	<b>AC: 110-240V, 50Hz</b>
Rated Load:	<b>12W (24PCS LED)</b>
Detection Distance:	<b>max.6m(&lt;24°C)</b>
Time Delay:	<b>*10 sec to 3 min</b>
Luminous Flux:	<b>800lm</b>
Body Type:	<b>ABS+Plastic+PMMA</b>
IP Rating:	<b>IP20</b>
Dimension:	<b>Ø290 x 60mm</b>



*\*Can be customized*



## Led Dome Light

**8W** VT-8014


1267 - 3000K Warm White  
1266 - 4500K Day White  
1268 - 6000K White

BOX QTY.

**10**

EAN Code

3800157611893  
3800157611886  
3800157611909



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>110°</b>
Voltage/Frequency:	<b>AC:220-240V, 50/60Hz</b>	Color of Fixture:	<b>Black</b>
Luminous Flux:	<b>560lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Full Oval</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>126 x 187 x 76mm</b>
PF:	<b>&gt;0.5</b>		



## Led Dome Light

**12W** VT-8016


5056 - 4500K Day White  
5055 - 6000K White

BOX QTY.

**10**

EAN Code

3800157603980  
3800157603348



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC:220-240V, 50/60Hz</b>	Color of Fixture:	<b>Black</b>
Luminous Flux:	<b>840lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Full Oval</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>245 x 165 x 96mm</b>
PF:	<b>&gt;0.5</b>		





## Led Dome Light

**8W** VT-8014

1264 - 3000K Warm White

1263 - 4500K Day White

1265 - 6000K White

BOX QTY.


**10**

EAN Code

3800157611862

3800157611855

3800157611879



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>110°</b>
Voltage/Frequency:	<b>AC:220-240V, 50/60Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>560lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Full Oval</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>126 x 187 x 76mm</b>
PF:	<b>&gt;0.5</b>		



## Led Dome Light

**12W** VT-8016

5054 - 4500K Day White

5053 - 6000K White


BOX QTY.

**10**

EAN Code

3800157603331

3800157603324



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC:220-240V, 50/60Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>840lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Full Oval</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>245 x 165 x 96mm</b>
PF:	<b>&gt;0.5</b>		

**NEW**



### Led Dome Light

**12W** VT-8015

4998 - 3000K Warm White

5050 - 4500K Day White

4996 - 6000K White

**BOX QTY.**


**10**

EAN Code

3800157602549

3800157603294

3800157602228



Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP54	Shape:	Round
CRI:	>70	Dimension:	Ø220 x 105mm
PF:	>0.5		

**NEW**



### Led Dome Light

**12W** VT-8015

1349 - 3000K Warm White

5052 - 4500K Day White

5051 - 6000K White

**BOX QTY.**


**10**

EAN Code

3800157624066

3800157603317

3800157603300




Sensor Compatible:	Yes	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP54	Shape:	Round
CRI:	>70	Dimension:	Ø220 x 105mm
PF:	>0.5		



**IP65**  
RATED  
**Led Dome Light**  
12W VT-8008  
4980 - 6000K White

BOX QTY.  
**06**

EAN Code  
3800230629579



*\*Can be customized*

Sensor Type:	Microwave	Detection Distance:	*10%/50%/100%
Color:	Black	Time Delay:	*10s/1min/5min/10min/30min
Detection Range:	Max.(0 x H): 10m x 4m, 360°	Luminous Flux:	840lm
Voltage:	AC: 200-240V, 50/60Hz	Body Type:	ABS+Plastic+PMMA
Rated Load:	12W	IP Rating:	IP65
Sensor Compatible:	12W	Dimension:	Ø300 x 100mm


**IP66**  
RATED



**Led Dome Light**  
12W VT-8010  
1351 - 3000K Warm White  
1352 - 4000K Day White  
1353 - 6400K White

BOX QTY.  
**10**

EAN Code  
3800157624060  
3800157624077  
3800157624084



Sensor Compatible:	Yes	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP66	Shape:	Full Oval
CRI:	>70	Dimension:	242 x 165 x 96mm
PF:	>0.9		


**IP66**  
RATED



**Led Dome Light**  
12W VT-8010  
1350 - 3000K Warm White  
4973 - 4000K Day White  
1269 - 6400K White

BOX QTY.  
**10**

EAN Code  
3800157624053  
3800230629050  
3800157611916



Sensor Compatible:	Yes	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP66	Shape:	Full Oval
CRI:	>70	Dimension:	242 x 165 x 96mm
PF:	>0.9		



## Led Dome Light


**8W** VT-8014

4999 - 3000K Warm White  
1259 - 4500K Day White  
4997 - 6000K White

**BOX QTY.**  
 **10**

**EAN Code**

3800157602556  
3800157611817  
3800157602259



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>560lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>Ø180 x 82mm</b>
PF:	<b>&gt;0.5</b>		



## Led Dome Light


**8W** VT-8014

1261 - 3000K Warm White  
1260 - 4500K Day White  
1262 - 6000K White

**BOX QTY.**  
 **10**

**EAN Code**

3800157611831  
3800157611824  
3800157611848



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 200-240V, 50Hz</b>	Color of Fixture:	<b>Black</b>
Luminous Flux:	<b>560lm</b>	Body Type:	<b>Plastic Clad Aluminum</b>
IP Rating:	<b>IP54</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;70</b>	Dimension:	<b>Ø180 x 82mm</b>
PF:	<b>&gt;0.5</b>		



**NEW**



## LED Ceiling Dome Light Bling Star Cover

**BOX QTY.**

**20**

**8W** VT-8061

EAN Code

1370 - 3000K Warm White


3800157626262

1371 - 4000K Day White

3800157626279

1372 - 6400K White

3800157626286



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>560lm</b>	Body Type:	<b>Iron+PMMA</b>
IP Rating:	<b>IP20</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>Ø215 x 78mm</b>
PF:	<b>&gt;0.5</b>		

**NEW**



## LED Ceiling Dome Light Bling Star Cover

**BOX QTY.**

**10**

**12W** VT-8062

EAN Code

1373 - 3000K Warm White


3800157626293

1374 - 4000K Day White

3800157626309

1375 - 6400K White

3800157626316



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>840lm</b>	Body Type:	<b>Iron+PMMA</b>
IP Rating:	<b>IP20</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>Ø260 x 92mm</b>
PF:	<b>&gt;0.5</b>		

**NEW**



**LED Ceiling Dome Light  
Bling Star Cover**

**18W** VT-8063


- 1376 - 3000K Warm White
- 1377 - 4000K Day White
- 1378 - 6400K White

**BOX QTY.**

**10**

**EAN Code**

- 3800157626323
- 3800157626330
- 3800157626347



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>1260lm</b>	Body Type:	<b>Iron+PMMA</b>
IP Rating:	<b>IP20</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>Ø290 x 92mm</b>
PF:	<b>&gt;0.5</b>		

**NEW**



**LED Ceiling Dome Light  
Bling Star Cover**

**24W** VT-8064


- 1379 - 3000K Warm White
- 1380 - 4000K Day White
- 1381 - 6400K White

**BOX QTY.**

**10**

**EAN Code**

- 3800157626354
- 3800157626361
- 3800157626378



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Color of Fixture:	<b>White</b>
Luminous Flux:	<b>1680lm</b>	Body Type:	<b>Iron+PMMA</b>
IP Rating:	<b>IP20</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>Ø330 x 102mm</b>
PF:	<b>&gt;0.5</b>		

# Applications

Mostly used in Parking Lots, Corridors, Exterior Walls, Airports, and Malls.



## Sleek Design & Durability

Lightweight and energy efficient. Specially designed anti-glare diffuser.



2D LED Bulkhead



2D LED Bulkhead  
Emergency Battery Back Up



360°  
Detection Angle

2D LED Bulkhead  
with Microwave Sensor



360°  
Detection Angle

3IN1  
2D LED Bulkhead  
Built In Emergency Battery  
Back Up & Microwave Sensor



**NEW**

**2D LED Bulkhead**

**8W** VT-8039


1345 4000K Day White

EAN Code  
3800157623087

BOX QTY.  
 **10**



Watts:	<b>8W</b>
Lumens:	<b>720lm</b>
No. Of Led:	<b>40</b>
Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 260 x 90mm</b>
IP Rating:	<b>IP65</b>
Body Type	<b>Full PC</b>



**NEW**

**2D LED Bulkhead with Microwave Sensor**

**8W** VT-8041


1346 4000K Day White

EAN Code  
3800157623094

BOX QTY.  
 **10**



Watts:	<b>8W</b>
Lumens:	<b>720lm</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 260 x 90mm</b>
IP Rating:	<b>IP65</b>
Body Type	<b>Full PC</b>
Detection Angle:	<b>360° ceiling mounting ,120° wall mounting</b>
Detection Distance:	<b>3M, 5M, 8M, 10M optional</b>
Detection Range:	<b>Max D10M x 4M</b>
Hold Time:	<b>10Sec, 1min, 5min, 10min customized</b>
Day light Sensor:	<b>Day, 10LUX, 30LUX, 50LUX optional</b>
Dimmable Function:	<b>Yes, 0,10%, 20%, 30% optional</b>
Detection Motion Speed:	<b>0.5~3m/s</b>



**NEW**

**2<sub>1N1</sub>**

**2D LED Bulkhead  
Emergency Battery Backup**

**10W** VT-8042


1347 4000K Day White

EAN Code  
3800157623100

**BOX QTY.**  
**10**



**IP65  
RATED**



Watts:	<b>10W</b>
Lumens:	<b>720lm</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 260 x 100mm</b>
IP Rating:	<b>IP65</b>
Body Type:	<b>Full PC</b>
Emergency Operation time:	<b>&gt;3 Hours</b>
Emergency Standby Watts:	<b>&gt;1.2 Watts</b>
Battery Charging Current:	<b>60mA</b>
Battery Discharging Current:	<b>200mA</b>
Battery Type:	<b>Ni-CDAA, 7.2V 1.0Ah</b>
Charging indicate:	<b>Green LED</b>

**Including battery protection circuit & inhibiting mode**

**NEW**

**3<sub>1N1</sub>**

**2D LED Bulkhead  
Built In Emergency Battery  
Back Up & Microwave Sensor**

**10W** VT-8043


1348 4000K Day White

EAN Code  
3800157623117

**BOX QTY.**  
**10**



**IP65  
RATED**



Watts:	<b>10W</b>
Lumens:	<b>720lm</b>
Detection Angle:	<b>360° ceiling mounting ,120° wall mounting</b>
Detection Distance:	<b>3M, 5M, 8M, 10M optional</b>
Detection Range:	<b>Max D10M x 4M</b>
Hold Time:	<b>10S, 1min, 5min, 10min customized</b>
Day light Sensor:	<b>Day, 10LUX, 30LUX, 50LUX optional</b>
Dimmable Function:	<b>Yes, 0,10%, 20%, 30% optional</b>
Detection Motion Speed:	<b>0.5-3m/s</b>
IP Rating:	<b>IP65</b>
Body Type:	<b>Full PC</b>
Emergency Operation time:	<b>&gt;3 Hours</b>
Emergency Standby Watts:	<b>&gt;1.2 Watts</b>
Battery Charging Current:	<b>60mA</b>
Battery Discharging Current:	<b>200mA</b>
Battery Type:	<b>Ni-CDAA, 7.2V 1.0Ah</b>
Charging indicate:	<b>Green LED</b>

**Including battery protection circuit & inhibiting mode**

**NEW**

**2D LED Bulkhead**

**15W** VT-8044


1341 4000K Day White

EAN Code  
3800157623049

**BOX QTY.**  
 **10**



Watts:	<b>15W</b>
Lumens:	<b>1400lm</b>
No. Of Led:	<b>72</b>
Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 320 x 100mm</b>
IP Rating:	<b>IP65</b>
Body Type:	<b>Full PC</b>



**NEW**

**2D LED Bulkhead with Microwave Sensor**

**15W** VT-8045


1342 4000K Day White

EAN Code  
3800157623056

**BOX QTY.**  
 **10**



Watts:	<b>15W</b>
Lumens:	<b>1400lm</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 320 x 100mm</b>
IP Rating:	<b>IP65</b>
Body Type	<b>Full PC</b>
Detection Angle:	<b>360° ceiling mounting ,120° wall mounting</b>
Detection Distance:	<b>3M, 5M, 8M, 10M optional</b>
Detection Range:	<b>Max D10M x 4M</b>
Hold Time:	<b>105, 1min, 5min, 10min customized</b>
Day light Sensor:	<b>Day, 10LUX, 30LUX, 50LUX optional</b>
Dimmable Function:	<b>Yes, 0,10%, 20%, 30% optional</b>
Detection Motion Speed:	<b>0.5~3m/s</b>



**NEW**

**2<sub>IN</sub>1**

**2D LED Bulkhead**

**Emergency Battery Backup**

**17W** VT-8046

1343 4000K Day White


EAN Code

3800157623063

**BOX QTY.**  
**10**



**IP65**  
**RATED**



Watts:	<b>17W</b>
Lumens:	<b>1400lm</b>
Voltage/Frequency:	<b>AC: 200-240V, 50/60Hz</b>
On/Off Time:	<b>&lt;0.5s</b>
Life Span:	<b>30,000 Hours</b>
Unit Size:	<b>Ø 320 x 90mm</b>
IP Rating:	<b>IP65</b>
Body Type:	<b>Full PC</b>
Emergency Operation time:	<b>&gt;3 Hours</b>
Emergency Standby Watts:	<b>&gt;1.2 Watts</b>
Battery Charging Current:	<b>60mA</b>
Battery Discharging Current:	<b>200mA</b>
Battery Type:	<b>Ni-CDAA, 7.2V 1.0Ah</b>
Charging indicate:	<b>Green LED</b>

**Including battery protection circuit & inhibiting mode**

**NEW**

**3<sub>IN</sub>1**

**2D LED Bulkhead**

**Built In Emergency Battery Back Up & Microwave Sensor**

**17W** VT-8047

1344 4000K Day White


EAN Code

3800157623070

**BOX QTY.**  
**10**



**IP65**  
**RATED**



Watts:	<b>17W</b>
Lumens:	<b>1400lm</b>
Detection Angle:	<b>360° ceiling mounting ,120° wall mounting</b>
Detection Distance:	<b>3M, 5M, 8M, 10M optional</b>
Detection Range:	<b>Max D10M x 4M</b>
Hold Time:	<b>105, 1min, 5min, 10min customized</b>
Day light Sensor:	<b>Day, 10LUX, 30LUX, 50LUX optional</b>
Dimmable Function:	<b>Yes, 0,10%, 20%, 30% optional</b>
Detection Motion Speed:	<b>0.5~3m/s</b>
IP Rating:	<b>IP65</b>
Body Type:	<b>Full PC</b>
Emergency Operation time:	<b>&gt;3 Hours</b>
Emergency Standby Watts:	<b>&gt;1.2 Watts</b>
Battery Charging Current:	<b>60mA</b>
Battery Discharging Current:	<b>200mA</b>
Battery Type:	<b>Ni-CDAA, 7.2V 1.0Ah</b>
Charging indicate:	<b>Green LED</b>

**Including battery protection circuit & inhibiting mode**